

CARBOTROL

LOW PROFILE WASHWATER RECYCLE AND TREATMENT SYSTEMS

(Models GCW-1 GCW-2 WTD-11 WTD-12)



Engineered systems provide:

- * Best Available Technology*
- * Recycling or Discharge*
- * High Reliability and Low Maintenance*

Typical Applications:

- * Golf Course Maintenance*
- * Vehicle Washing*
- * Equipment Cleaning*



Carbtrol Corporation
955 Connecticut Ave., Suite 5202
Bridgeport, CT 06607
800.242.1150 - www.carbtrol.com

CARBOTROL

LOW PROFILE WASHWATER TREATMENT SYSTEM



PRIMARY COLLECTION SUMP

Dirty wash water collects in the primary sump. At water high level, the pump engages. During pumping, the water is vigorously agitated to ensure that grass, and dirt, do not accumulate in the sump.



TREATMENT SKID

Clarified water is pumped to a treatment unit where it is treated with granular activated carbon. Oxidation is provided as a polishing step where needed to meet treatment or recycle objectives objectives.



HYDROSCREEN AND GRASS CART

Dirty water is pumped from the primary sump to the solids separation hydroscreen. Grass trash and dirt are filtered by the screen and collected in a dump cart.

OIL WATER SEPARATOR / CLARIFIER

Filtered water is then discharged to the combination oil-water separator / clarifier where free hydrocarbons and fine solids are removed. Settled solids are dewatered in a sludge dewatering drum.